

현대 태양광 모듈

MG-Series

Multi-crystalline Type (다결정모듈)

HiS-M230MG (BK) | HiS-M235MG (BK) | HiS-M240MG (BK)

Mono-crystalline Type (단결정모듈)

HiS-S250MG (BK) | HiS-S255MG (BK) | HiS-S260MG (BK)

Mechanical Characteristics

Dimensions	983mm (38.7")(W) × 1,645mm (64.76")(L) × 35mm (1.38")(H)
Weight	Approx. 18.5kg (40.8lbs)
Solar cells	60 cells in series (6 × 10 matrix)
Output cables	4mm ² (12AWG) cables with polarized weatherproof connectors, IEC certified (UL listed), Length 1.0m (39.4")
Junction box	IP65, weatherproof, IEC certified (UL listed)
Bypass diodes	3 bypass diodes to prevent power decrease by partial shade
Construction	Front : High transmission low-iron tempered glass, 3.2mm (0.126") Encapsulant : EVA Back Sheet : Weatherproof film (Black)
Frame	Clear anodized aluminum alloy type 6063 (Black)

High Quality

- IEC 61215 (Ed.2) and IEC 61730 by TÜV Rheinland
- UL listed (UL 1703), Class C Fire Rating
- Output power tolerance +3/-0%
- ISO 9001:2000 and ISO 14001:2004 Certified
- Advanced Mechanical Test (5,400Pa) Passed (IEC)
/ Mechanical Load Test (40lbs/ft²) Passed (UL)
- Ammonia Corrosion Resistance Test Passed

Fast and Inexpensive Mounting


- Delivered ready for connection
- Pre-confectioned cables
- IEC (UL) certified and weatherproof connectors
- Integrated bypass diodes

Limited Warranty

- 10 years for product defect
- 10 years for 90% of warranted min. power
- 25 years for 80% of warranted min. power

※ 보증관련 유의사항

태양광모듈 보증은 현대중공업 로고와 시리얼 넘버가 부착된 정품 제품에만 유효합니다.



Electrical Characteristics

| Multi-crystalline Type (다결정모듈) |

		HIS-M□□□MG		
		230	235	240
Nominal output (Pmpp)	W	230	235	240
Voltage at Pmax (Vmpp)	V	30.1	30.3	30.5
Current at Pmax (Impp)	A	7.7	7.8	7.9
Open circuit voltage (Voc)	V	37.1	37.4	37.7
Short circuit current (Isc)	A	8.2	8.3	8.3
Output tolerance	%	+3/-0		
No. of cells & connections	pcs	60 in series		
Cell type	-	6" Poly-crystalline silicon		
Module efficiency	%	14.2	14.5	14.8
Temperature coefficient of Pmpp	%/K	-0.43	-0.43	-0.43
Temperature coefficient of Voc	%/K	-0.32	-0.32	-0.32
Temperature coefficient of Isc	%/K	0.048	0.048	0.048

※ All data at STC (Standard Test Conditions). Above data may be changed without prior notice.


| Mono-crystalline Type (단결정모듈) |

		HIS-S□□□MG		
		250	255	260
Nominal output (Pmpp)	W	250	255	260
Voltage at Pmax (Vmpp)	V	30.5	30.8	31.0
Current at Pmax (Impp)	A	8.2	8.3	8.4
Open circuit voltage (Voc)	V	37.5	37.7	37.8
Short circuit current (Isc)	A	8.7	8.8	8.9
Output tolerance	%	+3/-0		
No. of cells & connections	pcs	60 in series		
Cell type	-	6" Mono-crystalline silicon		
Module efficiency	%	15.5	15.8	16.1
Temperature coefficient of Pmpp	%/K	-0.45	-0.45	-0.45
Temperature coefficient of Voc	%/K	-0.33	-0.33	-0.33
Temperature coefficient of Isc	%/K	0.032	0.032	0.032


※ All data at STC (Standard Test Conditions). Above data may be changed without prior notice.

| Module Diagram |

(unit : mm, inch)



| I-V Curves |




| 설치시 유의사항 |

- 전문 기술자만이 설치 및 유지·보수 작업을 할 수 있으며 고압 직류전압에 유의하십시오.
- 모듈 뒷면이 상하거나 굽히지 않도록 유의하십시오.
- 모듈은 젖은 상태로 설치하지 마십시오.

Nominal Operating Cell Temperature	46°C ± 2
Operating Temperature	-40 - 85°C
Maximum System Voltage	DC 1,000V (IEC), DC 600V (UL)
Maximum Reverse Current	15A

[Printed Date : May 2013]



Sales & Marketing (솔라영업부)
 서울특별시 중로구 을곡로 75 현대빌딩 2층
 Tel : 02-746-8401, 8404, 7512, 7852, 4517 Fax : 02-746-7675

현대중공업